

Data of issue 05/02/2021 Printing date 04/08/2023 Revision 5 of 04/08/2023

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name: DEKAP Commercial code: 40.022

UFI code: 3C00-Y0RX-X003-9EC8

1.2 Identified uses of the substance or mixture and uses advised against

Detergent

Use: Professional Product categories:

Washing and cleaning products (including solvent-based products)

Uses advised against

Do not use for uses other than those indicated

1.3 Details of the supplier of the safety data sheet

Company name: Silpar TK snc

Address: Via Rosa Luxemburg 12/14

10093 - Collegno (TO)

Telephone: +39 011 7791177 Fax: +39 011 7791177

Email: sicurezza@silpartkline.com

1.4 Emergency telephone number

CAVp "Osp. Pediatrico Bambino Gesù - Roma Tel. +39 06 68593726 Az. Osp. Univ. Foggia Tel. +39 0881 732326 Az. Osp. "A. Cardarelli" - Napoli Tel. +39 081 7472870 CAV Policlinico "Umberto I" - Roma Tel. +39 06 49978000 CAV Policlinico "A. Gemelli" - Roma Tel. +39 06 3054343 Az. Osp. "Careggi" U.O. Tossicologia Medica - Firenze Tel. +39 055 7947819 CAV Centro Nazionale di Informazione Tossicologica - Pavia Tel. +39 0382 24444 Tel. +39 02 66101029 Osp. Niguarda Ca' Granda - Milano Azienda Ospedaliera Papa Giovanni XXII - Bergamo Tel. +39 800883300 Azienda Ospedaliera Universitaria Integrata Verona Tel. +39 800 011858

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Reg. EU n°1272/2008 [CLP]

Skin Irrit. 2, H315 Eye Irrit. 2, H319

2.2 Label elements

Hazard pictograms:



Signal word: Warning

Hazard statements: H315 Causes skin irritation.

H319 Causes serious eye irritation.



Data of issue 05/02/2021

Printing date 04/08/2023

Revision 5 of 04/08/2023

Precautionary statements:

P280 Wear protective gloves/ protective clothing / eye protection / face protection.

P302 + P352 IF ON SKIN: Wash with plenty of water

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.
P501 Dispose of contents/container in accordance with local/regional/ national/international

Regulation (EC) No. 648/2004:

<5% Perfumes ((r)-p-mentha-1,8-diene). Phosphates, EDTA and salts

2.3 Other hazards

Substance vPvB: None - Substance PBT: None

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

N.A.

3.2 Mixtures

1.CAS 2.N° EC 3.N° Index 4.N° REACH	Name	Weight (%)	Classification1272/2008 (CLP)	
1. 107-98-2 2. 203-539-1 3. 603-064-00-3 4. 01-2119457435-35-XXXX	1-methoxypropan-2-ol	3-5	Flam. Liq. 3 H226, STOT SE 3 H336	
1. 7320-34-5 2. 230-785-7 Tetrapotassiump 3. notAvailable sphate 4. 01-2119489369-18-XXXX		1-3	Eye Irrit. 2; H319	
1. 10213-79-3 2. 229-912-9 3. 014-010-00-8 4. 01-2119449811-37-XXXX	Disodiummetasilicatep entahydrate	1-3	Eye Dam. 1; H318 Skin Corr. 1B; H314 Met. Corr. 1; H290 STOT SE 3; H335	

The full text of the H phrases is given in section 16 of the safety data sheet

SECTION 4: FIRST AID MEASURES

4.1 Description of first aidmeasures

Eye contact Remove contact lenses, if present. Wash immediately with plenty of water for at least 15

minutes, opening the eyelids fully. If problem persists, seek medical advice.

Skin contact Remove contaminated clothing. Rinse skin with a shower immediately. Wash contaminated

clothing before using it again.

Ingestion Get medical advice/attention. Do not induce vomiting. Do not administer anything not

explicitly authorised by a doctor.

Inhalation Remove to open air. If unwell, contact a doctor.

4.2 Most important symptoms and effects, both acute and delayed

For symptoms and effects caused by the contained substances, see chap. 11.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT



Extinguishing substances are: carbon dioxide, foam, chemical powder.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water.

5.2 Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3 Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2 Environmentalprecautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3 Methods and material for containment and cleaning up

Absorb the remainder with inert absorbent material. Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4 Reference to other sections

Refer to sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2 Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3 Specific end use(s)

See section 1.2

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Occupational Exposure Limits

1-methoxypropan-2-ol

EU Consolidated List of Indicative Occupational Exposure Values (VLIEP)

Data of issue 05/02/2021

Printing date 04/08/2023

Revision 5 of 04/08/2023



Safety data sheet

According to Regulation (EC) 1907/2006 - Regulation (EC) 878/2020

TWA: 100 ppm / 375 mg / m3 STEL: 568 mg / m3 / 100 ppm Occupational Exposure Limits TWA: 100 ppm / 375 mg / m3 STEL: 568 mg / m3 / 100 ppm

Tetrapotassium pyrophosphate

EU Consolidated List of Indicative Occupational Exposure Values (VLIEP)

TWA: 4 mg / m3

Derived No effect level (DNEL)

1-methoxypropan-2-ol

Dermal 183 mg / kg bw / day (Systemic, chronic) Inhalation 369 mg / m³ (Systemic, chronic) Inhalation 553.5 mg / m³ (Systemic, acute) Inhalation 553.5 mg / m³ (Local, acute) Dermal 78 mg / kg bw / day (Systemic, chronic)* Inhalation 43.9 mg / m³ (Systemic, chronic)* Oral 33 mg / kg bw / day (Systemic, chronic)*

Tetrapotassium pyrophosphate

Inhalation 17.63 mg/m³ (Local, chronic) Inhalation 4.35 mg/m³ (Systemic, chronic)*

Disodium metasilicate pentahydrate

Dermal 1.49 mg / kg bw / day (Systemic, chronic) Inhalation 6.22 mg / m³ (Systemic, chronic) Dermal 0.74 mg / kg bw / day (Systemic, chronic)* Inhalation 1.55 mg / m³ (Systemic, chronic)* Oral 0.74 mg / kg bw / day (Systemic, chronic)*

Predicted No Effect Concentration (PNEC)

1-methoxypropan-2-ol

10 mg / L (Fresh water)
1 mg / L (Water - intermittent release)
100 mg / L (Water (Marine))
52.3 mg / kg sediment dw (Sediment (Freshwater))
5.2 mg / kg sediment dw (Sediments (Marine))
4.59 mg / kg soil dw (Soil)
100 mg / L (STP)

Tetrapotassium pyrophosphate

0.05 mg / L (Freshwater)
0.5 mg / L (Water - periodic release)
0 mg / L (Water (Marine))
50 mg / L (STP)

Disodium metasilicate pentahydrate

7.5 mg / L (Freshwater) 1 mg / L (Water - intermittent release) 7.5 mg / L (Water (Marine)) 1000 mg / L (STP)

8.2 Exposure controls

Hands protection

Protective gloves ompliant with standard EN 374

For the final choice of the material of the work gloves it is necessary to consider: compatibility, degradation, breakage time and permeation.

In the case of preparations, the resistance of work gloves to chemical agents must be checked before use as it is not foreseeable. Gloves have a wear time that depends on the duration and method of use.

Pagina**4** di**10**

Data of issue 05/02/2021 Printing date 04/08/2023 Revision 5 of 04/08/2023

^{*} Values that refer to the population

Respiratoryprotection

According to Regulation (EC) 1907/2006 - Regulation (EC) 878/2020

Data of issue 05/02/2021

Printing date 04/08/2023 Revision 5 of 04/08/2023

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type A filter combined with a type P filter should be worn (see standard EN 14387). Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

In the event that the substance in question is odorless or its olfactory threshold is higher than the relative exposure limit and in case of emergency, or when the exposure levels are unknown or the concentration of oxygen in the work environment is less than 17% by volume, wear an open-circuit compressed air self-contained breathing apparatus (ref. standard EN 137) or respirator with external air intake for use with a full face mask, half mask or mouthpiece (ref. standard EN 138). Provide an eye wash and emergency shower system.

The product must be used in highly ventilated environments and in the presence of strong localized aspirations, otherwise use the personal protective equipment indicated.

Eye and face protection

Wear protective goggles (see standard EN 166).

Body and skin protection:

Wear professional long-sleeved overalls and safety footwear (see Regulation 2016/425

and standard EN ISO 20344).

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance:	Liquid
Colour:	Colorless

Odour:	Perfumed
Odourthreshold:	N.A.
pH:	11.5
Melting point/freezing point:	N.A.
Initial boiling point and boiling range:	N.A.
Flash point:	N.A.
Evaporation rate:	N.A.
Flammability (solid, gas):	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour pressure:	N.A.
Vapourdensity (Air=1):	N.A.
Relative density (Water=1):	1,02 Kg/I
Solubility(ies):	Soluble
Partition coefficient: n-octanol/water:	N.A.
Auto-ignition temperature (°C):	N.A.
Decomposition temperature:	N.A.
Viscosity:	N.A.
Explosiveproperties:	Non-explosive product
Oxidisingproperties:	N.A.

9.2 Other information

Information notavailable

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

disodium metasilicate pentahydrate:



Data of issue 05/02/2021

Printing date 04/08/2023 Revision 5 of 04/08/2023

According to Regulation (EC) 1907/2006 - Regulation (EC) 878/2020

Aqueous solutions react with aluminum, zinc, tin, copper and their alloys to produce hydrogen which is its own time can form explosive mixtures in contact with air.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No dangerous reactions are expected

10.4 Conditions to avoid

Avoid exposing the product to high temperatures.

1-methoxy-2-propanol:

The product can decompose on exposure to high temperatures. Gas formation during decomposition can cause compression in closed systems. Avoid electrostatic discharges.

Tetrapotassium pyrophosphate:

Keep away from acidic and oxidizing materials.

disodium metasilicate pentahydrate:

Hygroscopic product. Contact with water and moisture can cause it to agglomerate and harden.

10.5 Incompatiblematerials

Ammonia. Reactive metals. Strong bases.

10.6 Hazardousdecomposition products

It does not decompose when used for its intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Unless otherwise specified, the data required by Regulation (EU) 2020/878 indicated below are to be understood N.A.:

(a) acute toxicity;

1-methoxypropan-2-ol

LD50 (Oral)> 2000 mg / kg

LD50 (Dermal)> 5000 mg / kg

tetrapotassium-pyrophosphate

LD50 (Oral)> 2000mg / kg (Rat)

LD50 (Dermal)> 2000mg / kg (Rabbit)

LC50 (Inhalation)> 1.1mg / kg (Rat)

Disodium metasilicate pentahydrate

LD50 (Oral) 1152 - 1349 mg / kg dw (Mouse)

LD50 (Dermal)> 5000mg / kg (Rat)

LC50 (Inhalation)> 2.06 mg / I mg / kg (Rat)

(b) skin corrosion/irritation;

The product is classified as Skin Irrit. 2, H315

(c) serious eye damage/irritation;

The product is classified Eye Irrit. 2, H319

(d) respiratory or skin sensitisation;

(e) germ cell mutagenicity;

(f) carcinogenicity;

(g) reproductive toxicity;

(h) STOT-single exposure;

(i) STOT-repeated exposure;

(j) aspiration hazard.

11.2 Information on other hazards

Information not available

SECTION 12: ECOLOGICAL INFORMATION



Data of issue 05/02/2021 Printing date 04/08/2023 Revision 5 of 04/08/2023

12.1 Toxicity

Endpoint	Duration	Species	Value			
1-methoxypropan-2-ol						
EC50	72h	Algae	>500mg/l			
EC50	48h	Crustaceans	23300mg/l			
LC50	96h	Fish	>=1000mg/l			
EC50	96h	Algae	>1000mg/l			
Tetrapotassium pyrophosphate						
EC50(ECx)	48h	Algae	>=100<=200mg/l			
EC50	72h	Algae	>100mg/l			
LC50	96h	Fish	>100mg/l			
EC50	48h	Crustaceans	>100mg/I			
Disodium metasilicate pentahydrate						
LC50	96h	Brachydanio rerio	>210mg/l			
EC50	48h	Daphnia magna	>1700mg/I			
EC50	72h	Scenedesmus subspicatus	>207mg/l			

12.2 Persistence and degradability

1-methoxypropan-2-ol

The material is easily biodegradable. Pass the (I) OECD test for immediate biodegradability.

10-day window period: OK Biodegradation: 96% Exposure time: 28 d

Method: OECD 301E test method guideline or equivalent

Photodegradation

Test type: Half-life (indirect photolysis)

Sensitizer: OH radicals Atmospheric half-life: 7.8 h

Method: estimated.

Tetrapotassium pyrophosphate:

The methods for determining the degradability are not applicable to inorganic substances.

disodium metasilicate pentahydrate:

Biodegradation

Dissolution-soluble inorganic silicates rapidly depolymerize into molecular species indistinguishable from dissolved natural silicas. They combine with the ions of Ca, Mg, Fe, Al and others to form insoluble compounds similar to the constituents of natural soils.

12.3 Bioaccumulative potential

1-methoxypropan-2-ol

The bioconcentration potential is low (BCF <100 or Log Pow <3).

Partition coefficient: n-octanol / water (log Pow): 0.37 at 20 ° C Measured

Bioconcentration factor (BCF): <2.

12.4 Mobility in soil

1-methoxypropan-2-ol

The potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 0.2 - 1.0 estimated.

12.5 Results of PBT and vPvB assessment

On the basis of available data, the product does not contain PBT or vPvB substances in percentage greater than 0.1%.

12.6 Endocrine disruptingproperties

No data available

12.7 Other adverseeffects



No data available

Data of issue 05/02/2021 Printing date 04/08/2023 Revision 5 of 04/08/2023

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. Avoid littering. Do not contaminate soil, sewers and waterways. Waste transportation may be subject to ADR restrictions. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14: TRANSPORT INFORMATION

14.1 UN number or ID number

N.A.

14.2 UN proper shipping name

ΝΔ

14.3 Transport hazard class(es)

N.A.

14.4 Packing group

N.A.

14.5 Environmental hazards

N.A.

14.6 Special precautions for user

N.A.

14.7 Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso Category - Directive 2012/18/EC:

None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation1907/2006.

Point 3

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisarion (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:



None.

Data of issue 05/02/2021 Printing date 04/08/2023 Revision 5 of 04/08/2023

Regulation (EC) Nr. 1357/2014 - waste:

HP4 - Irritant - Skin irritation and eye damage

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

Regulation (EC) No. 648/2004

Ingredients according to Regulation (EC) No. 648/2004

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

15.2 Chemical safetyassessment

A chemical safety assessment has been carried out for the following contained substances:

Tetrapotassium pyrophosphate

1-methoxypropan-2-ol

Disodium metasilicate pentahydrate

SECTION 16: OTHER INFORMATION

Full text of H codes mentioned in sections 2 - 3

H226 Flammable liquid and vapour

H290 May be corrosive to metals

H314 Causes severe skin burns and eye damage

H318 Causes serious eye damage

H319 Causes serious eye irritation

H335 May cause respiratory irritation;

H336 May cause drowsiness or dizziness

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit



- VOC: Volatile organic Compounds

- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation.

Data of issue 05/02/2021 Printing date 04/08/2023 Revision 5 of 04/08/2023

Classification and procedure used to derive it according to regulation (EC)1272/2008 [CLP] in relation to mixture:

Skin Irrit. 2, H315 - Calculation method Eye Irrit. 2, H319 - Calculation method

GENERAL BIBLIOGRAPHY

Regulation (EU) 1907/2006 of the European Parliament (REACH)

Regulation (EU) 1272/2008 of the European Parliament (CLP)

Regulation (EU) 2020/878 (Annex II REACH Regulation)

Regulation (EC) 790/2009 of the European Parliament (I Atp. CLP)

Regulation (EU) 286/2011 of the European Parliament (II Atp. CLP)

Regulation (EU) 618/2012 of the European Parliament (III Atp. CLP)

Regulation (EU) 487/2013 of the European Parliament (IV Atp. CLP)

Regulation (EU) 944/2013 of the European Parliament (V Atp. CLP) Regulation (EU) 605/2014 of the European Parliament (VI Atp. CLP)

Regulation (EU) 2015/1221 of the European Parliament (VI Atp. CLP)

Regulation (EU) 2016/918 of the European Parliament (VIII Atp. CLP)

Regulation (EU) 2016/1179 (IX Atp. CLP)

Regulation (EU) 2017/776 (X Atp. CLP)

Regulation (EU) 2018/669 (XI Atp. CLP)

Regulation (EU) 2019/521 (XII Atp. CLP)

Delegated Regulation (EU) 2018/1480 (XIII Atp. CLP)

Regulation (EU) 2019/1148

Delegated Regulation (EU) 2020/217 (XIV Atp. CLP)

Delegated Regulation (EU) 2020/1182 (XV Atp. CLP)

Delegated Regulation (EU) 2021/643 (XVI Atp. CLP)

Delegated Regulation (EU) 2021/849 (XVII Atp. CLP)

Delegated Regulation (EU) 2022/692 (XVIII Atp. CLP)

Regulation (EU) 2020/878 of the European Parliament

The Merck Index. - 10th Edition Handling Chemical Safety

INRS - Fiche Toxicologique (toxicological sheet)

Patty - Industrial Hygiene and Toxicology

N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition

ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Difference with the previous version:

Sections:01/02/03/04/05/06/07/08/09/10/11/12/13/14/15/16