

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name: TK 3
Product code: 40.006
UFI code: 3QSJ-F34U-000E-57K1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use:
Lubricant (aerosol)
Uses advised against:
Relevant uses are listed above. No other uses are recommended.

1.3 Details of the supplier of the safety data sheet

Company name: Silpar TK snc
Address: Via Rosa Luxemburg 12/14
10093 - Collegno (TO)
Telephone: +39 011 7791177
Fax: +39 011 7791177
Email: sicurezza@silpartkline.com

1.4 Emergency telephone number

CAVp "Osp. Pediatrico Bambino Gesù - Roma	Tel. +39 06 68593726
Az. Osp. Univ. Foggia	Tel. +39 0881 732326
Az. Osp. "A. Cardarelli" - Napoli	Tel. +39 081 7472870
CAV Policlinico "Umberto I" - Roma	Tel. +39 06 49978000
CAV Policlinico "A. Gemelli" - Roma	Tel. +39 06 3054343
Az. Osp. "Careggi" U.O. Tossicologia Medica - Firenze	Tel. +39 055 7947819
CAV Centro Nazionale di Informazione Tossicologica - Pavia	Tel. +39 0382 24444
Osp. Niguarda Ca' Granda - Milano	Tel. +39 02 66101029
Azienda Ospedaliera Papa Giovanni XXII - Bergamo	Tel. +39 800 883300
Azienda Ospedaliera Universitaria Integrata Verona	Tel. +39 800 011858

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Reg. EU n°1272/2008 [CLP]

Aerosols 1, H222+H229
Skin Irrit. 2 H315
STOT SE 3 H336
Aquatic Chronic 2 H411

2.2 Label elements



Hazard pictograms:

Signal word: Danger

Hazard statements: H222 Extremely flammable aerosol
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

- P101 If medical advice is needed, have product container or label at hand
- P102 Keep out of reach of children
- P103 Read label before use
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P261 Avoid breathing dust/fume/gas/mist/ vapours/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves and eye protection.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P501 Dispose of contents/container in accordance with local/regional/ national/international regulations

Contains:

Hydrocarbons, C6, isoalkanes, < 5% n-Hexane

Special provisions based on Annex XVII of REACH and subsequent adaptations:

Use reserved for professional users.

2.3 Other hazards

Substance vPvB: None - Substance PBT: None.

Aerosol containers exposed to temperatures above 50°C can deform and burst and be projected a considerable distance. The vapors are heavier than air and can localize in confined spaces, spread to the ground and can form flammable and explosive mixtures with air in the event of ignition even remotely, with consequent risk of fire. The aerosol contains an asphyxiating gas; avoid the accumulation of vapors in large quantities in confined environments as it can cause asphyxiation due to lack of oxygen. Exposure to high concentrations of vapours, particularly in confined and inadequately ventilated environments, can cause irritation to the respiratory tract, nausea, malaise and dizziness.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

N.A.

3.2 Mixtures

1.CAS 2.N° EC 3.N° Index 4.N° REACH	Name	Weight (%)	Classification 1272/2008 (CLP)
1. Not Available 2. 931-254-9 3. Not Available 4. 01-2119484651-34 -XXXX	Hydrocarbons, C6, isoalkanes, < 5% n- Hexane	40-50	Flam. Liq. 2 H225 Asp. Tox. 1 H304 Skin Irrit. 2 H315 STOT SE 3 H336 Aquatic Chronic 2 H411
1. 106-97-8 2. 203-448-7 3. 601-004-00-0 4. 01-2119474691-32 -XXXX	butane	20-25	Flam. Gas 1 H220 Press. Gas H280
1. 74-98-6 2. 200-827-9 3. 601-003-00-5 4. 01-2119486944-21-XXXX	Propane	12.5-15	Flam. Gas 1 H220 Press. Gas H280

1. 75-28-5 2. 200-857-2 3. 601-004-00-0 4. 01-2119485395-27-XXXX	Isobutane	7-10	Flam. Gas 1H220 Press. Gas H280
---	-----------	------	------------------------------------

The full text of the H phrases is given in section 16 of the safety data sheet

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

Eye contact	In case of contact with the eyes, rinse them with water for an adequate amount of time and keeping the eyelids open, then immediately consult an ophthalmologist. Protect the uninjured eye.
Skin contact	Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.
Ingestion	Do not under any circumstances induce vomiting. SEEK MEDICAL EXAMINATION IMMEDIATELY
Inhalation	Remove to open air. If unwell, contact a doctor.

4.2 Most important symptoms and effects, both acute and delayed

For symptoms and effects caused by the contained substances, see chap. 11.

4.3 Indication of any immediate medical attention and special treatment needed

In the event of an accident or discomfort, consult a doctor immediately (if possible show the instructions for use or the safety data sheet).

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water.

5.2 Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3 Advice for firefighters

The heat causes an increase in pressure inside the container with the risk of bursting.

In the event of a fire, the aerosols, when they explode, can be projected violently at a distance, with the risk of spreading the fire.

Use suitable respiratory equipment.

Collect the contaminated water used to extinguish the fire separately. Do not discharge it into the sewer system.

If feasible from a safety point of view, move undamaged containers from the area of immediate danger.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

For those not directly involved:

Eliminate any sources of ignition (cigarettes, flames, sparks, electricity, etc.) or heat from the area where the leak occurred and provide adequate ventilation. Evacuate the surrounding areas and prevent the entry of external and unprotected personnel. Notify emergency crews.

Stop the leak if there is no danger. Do not handle damaged containers or spilled product without first wearing appropriate protective equipment. Avoid breathing vapors or mist. For information relating to environmental and health risks, respiratory protection, ventilation and individual means of protection, refer to section 8.

For those directly involved:

Emergency workers are recommended to wear appropriate personal protective equipment as indicated in section 8. Vapors are heavier than air and, in the event of spills, can accumulate in enclosed spaces and low areas where

they can easily ignite. If the situation cannot be fully assessed or if there is a risk of oxygen deficiency, use only a self-contained breathing apparatus (Type EN137).

6.2 Environmental precautions

Prevent the product from spilling or entering drains or waterways. Spills or uncontrolled discharges into watercourses should be reported immediately to the Environment Agency or other appropriate regulatory body.

6.3 Methods and material for containment and cleaning up

Absorb the remainder with inert absorbent material. Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4 Reference to other sections

Refer to sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Pressurized container. Do not pierce or burn, even after use. Do not use in the presence of open flames or other sources of ignition. Not smoking. Avoid the accumulation of electrostatic charges. Do not spray on flames or incandescent bodies. Do not spray on hot surfaces.

USE ONLY IN A WELL-VENTILATED PLACE.

Vapors can ignite with explosion. It is therefore necessary to avoid their accumulation by keeping doors and windows open and ensuring good cross-ventilation. The vapors are heavier than air and can accumulate on the ground and, without adequate ventilation, if triggered, can ignite even remotely with the risk of backfire. Protect from sunlight. Do not expose to temperatures above 50°C/122°F.

Avoid contact with skin and eyes, inhalation of vapors and mists.

Environmental protection measures:

Minimize the release of the mixture into the air and the surrounding environment, avoiding accidental spills and keeping the product stored away from sewer drains.

Work hygiene precautions:

Contaminated clothing must be changed before entering dining areas. While working, do not eat, drink or smoke in work areas. Wash your hands after using the product. Avoid contact with skin and eyes, inhalation of vapors and mists. Do not use empty containers before they have been cleaned. Before transferring operations, make sure that there are no residual incompatible materials in the containers. Please also refer to paragraph 8 for the recommended protective devices.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Store in a well-ventilated place away from direct sunlight.

Recommended storage temperature: 15°C to 30°C.

Keep sparks, heat sources and any source of combustion away from open flames.

Keep containers in a vertical and safe position avoiding the possibility of falls or impacts.

Do not store the product in corridors and stairwells. Store the product only in original and closed packaging, not puncture or open aerosol containers. Keep away from food, drink and feed.

Incompatible materials:

DO NOT store together with oxidising, self-igniting, self-heating substances, organic peroxides, oxidizers, pyrophoric liquids and solids, explosives. See also the following paragraph 10.

Indication for locals:

Fresh and adequately ventilated. Avoid the accumulation of electrostatic charges.

Storage Classes:

Refer to section 15.1 for Storage Classes/Limits (Seveso III).

7.3 Specific end use(s)

See section 1.2

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 Control parameters**

Control parameters

Hydrocarbons, C6, isoalkanes, < 5% n-Hexane

TLV TWA - 1200 mg/m³

butane - CAS: 106-97-8

ACGIH - STEL: 1000 ppm - Notes: (EX) - CNS impair

propane - CAS: 74-98-6

ACGIH - Notes: (D, EX) - Asphyxia

isobutane - CAS: 75-28-5

ACGIH - STEL: 1000 ppm - Notes: (EX) - CNS impair

Derived No Effect Level (DNEL)**Hydrocarbons, C6, isoalkanes, < 5% n-Hexane**

Consumer: 1301 mg/kg - Exposure: Human Oral - Frequency: Long term, systemic effects - Notes: bw/day

Industrial worker: 13964 mg/m³ - Consumer: 1377 mg/kg - Exposure: Human dermal - Frequency: Long term, systemic effects - Notes: bw/dayIndustrial worker: 5306 mg/m³ - Consumer: 1137 mg/m³ - Exposure: Human inhalation - Frequency: Long term, systemic effects - Notes: bw/day**PNEC exposure limit values**

Information not available

Technical controls

Ensure adequate ventilation, especially in confined areas.

Make sure eye washers and showers are close to the workplace.

Use anti-exposure equipment

Provide an emergency exit.

8.2 Exposure controls

Hands protection

Protect hands with category work gloves (ref. Standard EN 374).

For the final choice of the material of the work gloves it is necessary to consider: compatibility, degradation, breakage time and permeation.

In the case of preparations, the resistance of work gloves to chemical agents must be checked before use as it is not foreseeable. Gloves have a wear time that depends on the duration and method of use.

Respiratory protection

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387). Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

In the event that the substance in question is odorless or its olfactory threshold is higher than the relative exposure limit and in case of emergency, or when the exposure levels are unknown or the concentration of oxygen in the work environment is less than 17% by volume, wear an open-circuit compressed air self-contained breathing apparatus (ref. standard EN 137) or respirator with external air intake for use with a full face mask, half mask or mouthpiece (ref. standard EN 138). Provide an eye wash and emergency shower system.

The product must be used in highly ventilated environments and in the presence of strong localized aspirations, otherwise use the personal protective equipment indicated

Eye and face protection

Wear protective goggles (see standard EN 166).

Body and skin protection:

Wear professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344).

Safety data sheet

TK3

According to Regulation (EC) 1907/2006 - Regulation 878/2020

Data of issue 09/02/2023

Printing date 31/10/2023

Revision 2 of 31/10/2023

Thermal risks:

Aerosol containers, if overheated, deform, burst and can be projected a considerable distance.

Environmental exposure controls:

Emissions from production processes and deriving from the use of the product, including those from ventilation equipment, should be controlled for the purposes of compliance with environmental protection legislation.

Product residues must not be discharged uncontrolled into waste water or waterways. For further information please refer to section 6.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance:	Liquid under pressure
Colour:	Transparent
Odour:	Characteristic of solvent
Odour threshold:	N.A.
pH:	N.A.
Melting point/freezing point:	N.A.
Initial boiling point and boiling range:	N.A.
Flash point:	< 0 °C
Evaporation rate:	N.A.
Flammability (solid, gas):	N.A.
Upper/lower flammability or explosive limits:	15 Vol % - 1.8 Vol %
Vapour pressure:	3-5 bar
Vapour density (Air=1):	2
Relative density (Water=1):	N.A.
Solubility(ies):	Insoluble in water
Partition coefficient: n-octanol/water:	N.A.
Auto-ignition temperature (°C):	> 300 °C
Decomposition temperature:	N.A.
Kinematic viscosity:	N.A.
Explosive properties:	N.A.
Oxidising properties:	N.A.

9.2 Other information

Information not available

9.2.1. Information with regard to physical hazard classes

Flammable aerosol

9.2.2. Other safety characteristics

Information not available

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

Stable under normal conditions.

10.2 Chemical stability

Pressurized container. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures above 50°C/122°F. Refer to the directions in section 7 for handling and storage.

10.3 Possibility of hazardous reactions

Under normal conditions of use and storage, dangerous reactions are not foreseeable. If released, vapors can form explosive mixtures with air. If overheated, aerosol containers can deform, burst and be projected a considerable distance.

10.4 Conditions to avoid



Safety data sheet

TK3

According to Regulation (EC) 1907/2006 - Regulation 878/2020

Avoid overheating.

Data of issue 09/02/2023

Printing date 31/10/2023

Revision 2 of 31/10/2023

10.5 Incompatible materials

Avoid contact with oxidizing materials. The product could catch fire. Avoid contact with strong reductants and oxidants, strong acids and bases, high temperature materials.

10.6 Hazardous decomposition products

It does not decompose when used for its intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Unless otherwise specified, the data required by Regulation (EU) 878/2020 indicated below are to be understood N.A.:

Toxicological information regarding the product:

TK 3

a) acute toxicity

Not classified

Based on available data, the classification criteria are not met.

b) skin corrosion/irritation

The product is classified: Skin Irrit. 2 H315

c) serious eye damage/serious eye irritation

d) respiratory or skin sensitization

Not classified

Based on available data, the classification criteria are not met.

e) mutagenicity of germ cells

Not classified

Based on available data, the classification criteria are not met.

f) carcinogenicity

Not classified

Based on available data, the classification criteria are not met.

g) reproductive toxicity

Not classified

Based on available data, the classification criteria are not met.

h) specific target organ toxicity (STOT) – single exposure

The product is classified: STOT SE 3 H336

(i) specific target organ toxicity (STOT) – repeated exposure

j) danger in case of aspiration

Not classified

Based on available data, the classification criteria are not met.

Toxicological information regarding the main substances present in the product:

Hydrocarbons, C6, isoalkanes, < 5% n-Hexane

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 20 mg/l - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 3000 mg/kg

Further information:

Vapor concentrations above recommended exposure levels are irritating to the eyes and respiratory tract, may cause headache and dizziness, have an anesthetic effect and cause other effects on the central nervous system.

Repeated and/or prolonged skin contact with low viscosity materials can degrease the skin with possible development of irritation and dermatitis. Small quantities of liquid, aspirated into the lungs in case of ingestion or vomiting, can cause chemical pneumonitis or pulmonary edema.

butane - CAS: 106-97-8

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat 658 mg/l - Duration: 4h

propane - CAS: 74-98-6

a) acute toxicity:

Safety data sheet

TK3

According to Regulation (EC) 1907/2006 - Regulation 878/2020

Test: LC50 - Route: Inhalation - Species: Rat 658 mg/l - Duration: 4h

b) skin corrosion/irritation:

No irritating and corrosive effects on the skin and mucous membranes.

c) serious eye damage/serious eye irritation:

Contact with liquefied gas can cause cold burns.

Data of issue 09/02/2023

Printing date 31/10/2023

Revision 2 of 31/10/2023

11.2 Information on other hazards

Flammable product and dangerous for the environment

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

The product is classified: Aquatic Chronic 3 - H412

Hydrocarbons, C6, isoalkanes, < 5% n-Hexane

a) Acute aquatic toxicity:

Endpoint: LC50 - Species: Oryzias latipes > 1 mg/l - Duration h: 48

Endpoint: LC50 - Species: Daphnia magna = 3.87 mg/l - Duration h: 48

Endpoint: ErL50 - Species: Algae (Pseudokirchneriella subcapitata) = 55 mg/l - Duration h: 72

Endpoint: NOEC - Species: Algae (Pseudokirchneriella subcapitata) = 30 mg/l - Duration h: 72

12.2 Persistence and degradability

Hydrocarbons, C6, isoalkanes, < 5% n-Hexane

Biodegradability: Rapidly degradable

12.3 Bioaccumulative potential

Information not available

12.4 Mobility in soil

Information not available

12.5 Results of PBT and vPvB assessment

On the basis of available data, the product does not contain PBT or vPvB substances in percentage greater than 0.1%.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

No data available

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. Avoid littering. Do not contaminate soil, sewers and waterways. Waste transportation may be subject to ADR restrictions. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

Additional disposal information:

CER CODE = 160504

SECTION 14: TRANSPORT INFORMATION

14.1 UN number or ID number

ADR-UN number: 1950

IATA-Un number: 1950

Safety data sheet

TK3

According to Regulation (EC) 1907/2006 – Regulation 878/2020

IMDG-Un number: 1950

Data of issue 09/02/2023

Printing date 31/10/2023

Revision 2 of 31/10/2023

14.2 UN proper shipping name

ADR-Shipping Name: Aerosol

IATA-Technical name: Aerosol

IMDG-Technical name: Aerosol

14.3 Transport hazard class(es)



ADR-Class: 2 5F

ADR-Label: 2

ADR - Hazard identification number: -

IATA-Class: 2.1

IATA-Label: 2.1

IMDG-Class: 2

14.4 Packing group

ADR-Packing Group: -

IATA-Packing group: -

IMDG-Packing group: -

14.5 Environmental hazards

Marine pollutant: Yes

14.6 Special precautions for user

IATA-Passenger Aircraft: ---

IATA-Cargo Aircraft: 203

IMDG-Technical name: Aerosol

IMDG-Page: F-D, S-U

14.7 Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso Category - Directive 2012/18/EC:

P3a, E2

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Restrictions related to the product:

Restriction 3

Restriction 40

Substances subject to authorisation (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for the mixture

SECTION 16: OTHER INFORMATION**Full text of H codes mentioned in sections 2 - 3**

- H220 Highly flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation.

Classification and procedure used to derive it according to regulation (EC) 1272/2008 [CLP] in relation to mixture:

- Aerosol 1, H222, H229 - Based on experimental tests
- Skin irritation 2, H315 - Calculation method
- STOT SE 3, H336 - Calculation method
- Aquatic Chronic 2 H411 - Calculation method

GENERAL BIBLIOGRAPHY

- Regulation (EU) 1907/2006 of the European Parliament (REACH)
- Regulation (EU) 1272/2008 of the European Parliament (CLP)
- Regulation (EU) 2020/878 (Annex II REACH Regulation)
- Regulation (EC) 790/2009 of the European Parliament (I Atp. CLP)



Safety data sheet

TK3

According to Regulation (EC) 1907/2006 – Regulation 878/2020

Regulation (EU) 286/2011 of the European Parliament (II Atp. CLP)
Regulation (EU) 618/2012 of the European Parliament (III Atp. CLP)
Regulation (EU) 487/2013 of the European Parliament (IV Atp. CLP)
Regulation (EU) 944/2013 of the European Parliament (V Atp. CLP)
Regulation (EU) 605/2014 of the European Parliament (VI Atp. CLP)
Regulation (EU) 2015/1221 of the European Parliament (VII Atp. CLP)
Regulation (EU) 2016/918 of the European Parliament (VIII Atp. CLP)
Regulation (EU) 2016/1179 (IX Atp. CLP)
Regulation (EU) 2017/776 (X Atp. CLP)
Regulation (EU) 2018/669 (XI Atp. CLP)
Regulation (EU) 2019/521 (XII Atp. CLP)
Delegated Regulation (EU) 2018/1480 (XIII Atp. CLP)
Regulation (EU) 2019/1148
Delegated Regulation (EU) 2020/217 (XIV Atp. CLP)
Delegated Regulation (EU) 2020/1182 (XV Atp. CLP)
Delegated Regulation (EU) 2021/643 (XVI Atp. CLP)
Delegated Regulation (EU) 2021/849 (XVII Atp. CLP)
Delegated Regulation (EU) 2022/692 (XVIII Atp. CLP)
Regulation (EU) 2020/878 of the European Parliament

The Merck Index. - 10th Edition
Handling Chemical Safety
INRS - Fiche Toxicologique (toxicological sheet)
Patty - Industrial Hygiene and Toxicology
N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products

Changes compared to the previous version:

01/02/03/04/05/06/07/08/09/10/11/12/13/14/15/16

Data of issue 09/02/2023

Printing date 31/10/2023

Revision 2 of 31/10/2023